



Noble Earth Technologies

Invisible Solvent Guard

MATERIAL SAFETY DATA SHEET

COMPANY DETAILS

Company Name & Address: Noble Earth Technologies
PO BOX 1733
Double bay 1360
Sydney NSW
P: 02 9316 8800
F: 02 9316 8600
E: info@nobleearth.com.au
Contact Name: Harry Pearsall

Not classified as hazardous according to the criteria of NOHSC Australia.

I IDENTIFICATION

Product Name: Noble Earth Technologies Invisible Solvent Guard
Other Names: Proper Shipping Name is FLAMMABLE LIQUID, N.O.S.
Product Code: None.
UN No: 1993 Hazchem Code: 3[Y]
Dangerous Goods Class: 3 Flammable Liquid
Sub Risk Class: None allocated
Packaging Group: III
Poison Schedule: S5
Chemical Family: Water solution of ingredients (see below).
Uses: Concrete sealant.

Physical Appearance & Properties

Appearance & Odour: Milky white liquid. Very mild odour.
Melting/softening point: Approximately 0°C.
Boiling point and vapour pressure: Approximately 100°C at 100kPa.
Volatile materials: Water component.
Flashpoint: 24c
Specific gravity: No data.
Solubility in water: Completely soluble.
Corrosiveness: Not corrosive.

Ingredients:

Chemical entity	CAS No	Proportion %	Worksafe Exposure Limits	
			TWA mg/m ³	STEL mg/m ³
Xylene	133-20-7	no data	350	655
Non hazardous silcones	no data	approx 5	not set	not set
Solvent naptha (petroleum), light arom.	64742-95-6	no data	not set	not set

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

II HEALTH HAZARD DATA

Health Effects:

No specific data is available for the product for chronic exposure symptoms. The ingredients are not listed as carcinogenic in Worksafe's document "Exposure Standards for Atmospheric Contaminants in the Occupational Environment" (May 1995).

Acute Effects:

Swallowed: Data suggests that this product should present no significant problems to typical persons in normal use.

Eye: This product is mildly irritating to the eyes. It is likely to cause mild discomfort such as watering and redness of the eyes. However, this should quickly disappear once exposure is over.

Skin: This product may irritate skin. However, it is unlikely to cause any more than mild transient discomfort. It is also unlikely to cause any significant lasting effects.

Inhalation: Data suggests that this product should present no significant problems to typical persons in normal use.

First Aid:

If poisoning occurs, contact a Doctor or Poisons Information Centre. Phone 13 1126 from anywhere in Australia.

If swallowed, do NOT induce vomiting. Give a glass of water.

Eyes: If product gets in eyes, wash material from them with running water. If they begin watering or reddening, take special care in washing thoroughly.

Skin: If product gets on skin, thoroughly wash contacted areas. No further measures should normally be required unless irritation is noticed. If irritation persists, seek medical attention.

Inhalation: No first aid measures normally required. However, if vapours or mists have been inhaled, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

Advice to Doctor: Treat symptomatically. Note the nature of this product.

III PRECAUTIONS FOR USE

Exposure Standards:

A time weighted average (TWA) concentration for an 8 hour day, and 5 day week has not been established by NOHSC Australia for any of the major ingredients in this product. There is a blanket limit of 10mg/m³ for dusts or mists when limits have not otherwise been established. The nature of this product makes it unlikely that this level will be approached in normal use.

Engineering Controls:

In industrial situations, concentration values below the TWA value should be maintained. Values may be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify the process or environment to reduce the problem.

Personal Protection:

The following instructions are meant for people coming into frequent and lengthy contact with this product. For occasional use, take precautions suitable for the conditions under which the product is being used.

Respiratory Protection: It is usually safe to not use a dust mask or respirator protection on account of this product. However, if the product is being used in dusty or confined conditions, use of a mask or respirator may be preferred. For help in selecting suitable equipment, consult AS/NZS 1715.

Protective Gloves: Impermeable protective gloves should be worn when you are using this product, to prevent irritation. For help in selecting suitable equipment, consult AS 2161.

Eye Protection: Protective eyewear is suggested when using this product. It is always prudent to use protective eyewear. Consult AS1336 and AS/NZS 1337 for advice on Industrial Eye Protection.

Clothing: This product is essentially safe to use without special protective clothing. However, its use is recommended as a good industrial practice. Consult AS2919 for advice on Industrial Clothing.

Safety Boots: Wearing safety boots in industrial situations is advisory. Consult AS/NZS2210 for advice on Occupational Protective Footwear.

Always wash hands before smoking, eating or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Storage & Transport

No special storage and transport requirements. This product has no UN classification. Not a Scheduled Poison. Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames, and make sure that the product does not come into contact with substances listed under "Materials to avoid" below.

Spills & Disposals

Minor spills do not normally need any special cleanup measures. In the event of a major spill, prevent spillage from entering drains or water courses. As a minimum, wear overalls, goggles and gloves. Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage. Can be slippery on floors, especially when wet. Recycle containers wherever possible. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Dispose of only in accord with all regulations.

Fire & Explosion Hazard

There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.

Flashpoint: Does not burn.

Flammability limits: Not applicable. This product does not burn.

Extinguishing Media: This product does not burn. Use extinguishing media suited to the materials that are burning.

Special Fire Fighting procedures: When fighting fires involving significant quantities of this product, wear safety boots, non-flammable overalls, gloves, hat, goggles and respirator. All skin areas should be covered.

Unusual Fire & Explosion Hazards: Fire decomposition products from this product may form toxic mixtures in confined spaces. Likely to decompose only after heating to dryness followed by further strong heating.

Stability: This product is unlikely to spontaneously decompose.

Polymerisation: This product is unlikely to spontaneously polymerise.

Decomposition Products: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. silica.

Materials to avoid: No particular incompatibilities.

V OTHER INFORMATION

This MSDS is prepared in accord with the Worksafe Australia document "National Code of Practice for the Preparation of Material Safety Data Sheets", 1994.

National Poisons Information Centre: Dial 13 1126 (from anywhere in Australia)

This MSDS copyright © Kilford & Kilford Pty Ltd, December, 2006.

<http://www.kilford.com.au/> Phone (02)9251 4532